



MATERIAL SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY INFORMATION

Product Name: TRICK RACING GAS WOA

Manufacturer Information:

Sunoco, Inc. (R&M)
Ten Penn Center
1801 Market Street
Philadelphia, Pennsylvania, 19103-1699

Product Use:

Racing fuel

Emergency Phone Numbers:

Chemtrec (800) 424-9300
Sunoco Inc. (800) 964-8861

Information:

Product Safety Information (610) 859-1120

2. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS No.	Amount (Vol%)
LIGHT PETROLEUM DISTILLATE	8006-61-9	0 - 99.9
TOLUENE	108-88-3	0 - 30
XYLENE	1330-20-7	0 - 25
TERT-BUTYL ALCOHOL	75-65-0	0 - 10
CYCLOHEXANE	110-82-7	0 - 9
1,2,4-TRIMETHYLBENZENE	95-63-6	0 - 5
ETHYL BENZENE	100-41-4	0 - 5
N-HEXANE	110-54-3	0 - 5
NAPHTHALENE	91-20-3	0 - 5
BENZENE	71-43-2	0.1 - 4.9
TERT-AMYL METHYL ETHER	994-05-8	0 - 2
CUMENE	98-82-8	0 - 1
TETRAETHYL LEAD	78-00-2	0 - 0.15

EXPOSURE GUIDELINES (SEE SECTION 15 FOR ADDITIONAL EXPOSURE LIMITS)

	CAS No.	Governing Body	Exposure Limits		
TOLUENE	108-88-3	OSHA	C	300	ppm
BENZENE	71-43-2	ACGIH	STEL	2.5	ppm
BENZENE	71-43-2	OSHA	STEL	5	ppm
ETHYL BENZENE	100-41-4	ACGIH	STEL	125	ppm
NAPHTHALENE	91-20-3	ACGIH	STEL	15	ppm
XYLENE	1330-20-7	ACGIH	STEL	150	ppm
LIGHT PETROLEUM DISTILLATE	8006-61-9	ACGIH	STEL	500	ppm
BENZENE	71-43-2	ACGIH	TWA	0.5	ppm
BENZENE	71-43-2	OSHA	TWA	1	ppm

CUMENE	98-82-8	ACGIH	TWA	50	ppm
CUMENE	98-82-8	OSHA	TWA	50	ppm
CYCLOHEXANE	110-82-7	OSHA	TWA	300	ppm
ETHYL BENZENE	100-41-4	ACGIH	TWA	100	ppm
ETHYL BENZENE	100-41-4	OSHA	TWA	100	ppm
N-HEXANE	110-54-3	ACGIH	TWA	50	ppm
N-HEXANE	110-54-3	OSHA	TWA	500	ppm
NAPHTHALENE	91-20-3	ACGIH	TWA	10	ppm
NAPHTHALENE	91-20-3	OSHA	TWA	10	ppm
TOLUENE	108-88-3	ACGIH	TWA	50	ppm
TOLUENE	108-88-3	OSHA	TWA	200	ppm
XYLENE	1330-20-7	ACGIH	TWA	100	ppm
XYLENE	1330-20-7	OSHA	TWA	100	ppm
LIGHT PETROLEUM DISTILLATE	8006-61-9	ACGIH	TWA	300	ppm
TERT-BUTYL ALCOHOL	75-65-0	ACGIH	TWA	100	ppm
TERT-BUTYL ALCOHOL	75-65-0	OSHA	TWA	100	ppm

3. HAZARDS IDENTIFICATION

- EMERGENCY OVERVIEW**

Danger! Extremely flammable liquid and vapor. Vapors may cause flash fire or explosion. Harmful or fatal if swallowed. Pulmonary aspiration hazard. Product may enter lungs and cause damage. Harmful if inhaled. High vapor concentrations may cause drowsiness. May cause skin irritation. May cause eye irritation. Contains material or materials that can cause cancer.

Hazards Ratings:

Key: 0 = least, 1 = slight, 2 = moderate, 3 = high, 4 = extreme

	<u>Health</u>	<u>Fire</u>	<u>Reactivity</u>	<u>PPI</u>
NFPA	1	3	0	
HMIS	2	3	0	X

- POTENTIAL HEALTH EFFECTS**

- PRE-EXISTING MEDICAL CONDITIONS**

The following diseases or disorders may be aggravated by exposure to this product: Skin, Eye, Blood forming organs, Nervous system, Respiratory system, Lung (asthma-like conditions), Cardiovascular system,

- INHALATION**

Can cause severe central nervous system depression (including unconsciousness). High vapor concentrations are irritating to the eyes, nose, throat, and lungs. May cause headaches and dizziness. May cause serious disturbances of heart rhythm. Repeated excessive exposures may cause blood disorders such as anemia and leukemia. Contains a material that has been related to cancer in humans. Solvent "huffing/sniffing" (abuse) or intentional prolonged overexposure to high levels of vapors can produce abnormal behavior, convulsions, hallucinations, delirium, nervous system damage and sudden death.

LC50 (mg/l): no data

LC50 (mg/m3): no data

LC50 (ppm): no data

- SKIN**

May be absorbed through the skin in harmful amounts. Prolonged or repeated skin contact may cause irritation.

Draize Skin Score: no data Out of 8.0

LD50 (mg/kg): no data

- EYES**

Moderately irritating to the eyes.

▪ **INGESTION**

Product may be harmful or fatal if swallowed. Material is a pulmonary aspiration hazard. Material can enter lungs and cause damage. Irritating to mouth, throat, and stomach.

LD50 (g/kg): no data

4. FIRST AID MEASURES

• **INHALATION**

Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen and continue to monitor. Get immediate medical attention.

• **SKIN**

Wash with soap and water. Get medical attention if irritation develops or persists. Injection injuries may not appear serious at first but within a few hours, without proper treatment, the area will become swollen, discolored and extremely painful. Wash clothing before reuse. Destroy contaminated shoes and other leather products.

• **EYES**

Flush eye with water for 15 minutes. Get medical attention.

• **INGESTION**

Do not induce vomiting! Do not give liquids! Get medical attention immediately.

5. FIRE FIGHTING MEASURES

• **EXTINGUISHING MEDIA**

Water spray Regular foam Dry chemical Carbon dioxide

• **FIRE FIGHTING INSTRUCTIONS**

Cool tank and container. Wear structural fire fighting gear.

FLAMMABLE PROPERTIES

	Typical	Minimum	Maximum	Text Result	Units	Method
Flash Point				MINUS 40 EST'D	F	N/A
Autoignition Temperature				850 ESTIMATED	F	N/A
Lower Explosion Limit	1.5				%	N/A
Upper Explosion Limit	7.6				%	N/A

6. ACCIDENTAL RELEASE MEASURES

Prevent ignition, stop leak and ventilate the area. Contain spilled liquid with sand or earth. DO NOT use combustible materials such as sawdust. Vapor can be controlled using a water fog. Water streams should not be directed to the liquid as this will cause the liquid to boil and generate more vapor. Keep personnel upwind from leak. Use appropriate personal protective equipment as stated in Section 8 of this MSDS. Advise the Environmental Protection Agency (EPA) and appropriate state agencies, if required. Absorb spill with inert material (e.g., dry sand or earth), then place in a chemical waste container. Vacuum or sweep up material and place in a disposal container.

7. HANDLING AND STORAGE

• **HANDLING**

Use only in a well-ventilated area. Ground and bond containers when transferring material. NFPA class IA storage. Flash point is less than 73 degrees F and boiling point is less than 100 degrees F. Avoid breathing (dust, vapor, mist, gas). Avoid prolonged or repeated contact with skin. Avoid contact with eyes. Wash thoroughly after handling. Never siphon by mouth.

• **STORAGE**

Keep away from heat, sparks, and flame. Keep container closed when not in use. Consult NFPA and / or OSHA codes for additional information.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Consult With a Health and Safety Professional for Specific Selections

- **ENGINEERING CONTROLS**

Use with adequate ventilation. Good general ventilation should be sufficient to control airborne levels.

- **PERSONAL PROTECTION**

- **EYE PROTECTION**

Use chemical splash goggles and face shield (ANSI Z87.1 or approved equivalent).

- **GLOVES or HAND PROTECTION**

The glove(s) listed below may provide protection against permeation. Gloves of other chemically resistant materials may not provide adequate protection. Protective gloves are recommended to protect against contact with product. Polyethylene; Neoprene; Nitrile; Polyvinyl alcohol; Viton;

- **RESPIRATORY PROTECTION**

Concentration in air determines the level of respiratory protection needed. Use only NIOSH certified respiratory equipment. Half-mask air purifying respirator with organic vapor cartridges is acceptable for exposures to ten (10) times the exposure limit. Full-face air purifying respirator with organic vapor cartridges is acceptable for exposures to fifty (50) times the exposure limit. Exposure should not exceed the cartridge limit of 1000 ppm. Protection by air purifying respirators is limited. Use a positive pressure-demand full-face supplied air respirator or SCBA for exposures greater than fifty (50) times the exposure limit. If exposure is above the IDLH (Immediately Dangerous to Life and Health) or there is the possibility of an uncontrolled release, or exposure levels are unknown, then use a positive pressure-demand full-face supplied air respirator with escape bottle or SCBA. Wear a NIOSH/MSHA-approved (or equivalent) full-facepiece airline respirator in the positive pressure mode with emergency escape provisions.

- **OTHER**

Where splashing is possible, full chemically resistant protective clothing (e.g., acid suit) and boots are required. The following materials are acceptable for use as protective clothing: Polyvinyl alcohol (PVA); Polyethylene; Neoprene; Nitrile; Viton; Polyurethane; Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower. Remove contaminated clothing and wash before reuse. For non-fire emergencies, positive pressure SCBA and structural firefighter's protective clothing will provide only limited protection.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical Property	Typical	Units	Text Result	Reference
Appearance		N/A	BLUE LIQUID	
Boiling Point		F	100-400	
Bulk Density		lb/gal	no data	
Melting Point		F	no data	
Molecular Weight		g/mole	no data	
Octanol/Water Coefficient		N/A	no data	
pH		N/A	no data	
Specific Gravity	0.72	N/A		
Solubility In Water		wt %	NIL TO 15%	
Odor		N/A	GASOLINE ODOR.	
Odor Threshold		ppm	< 1	
Vapor Pressure		mmHg	325 - 525	@ 20 C
Viscosity (F)		SUS	no data	
Viscosity (C)		CsT	no data	
% Volatile	100	wt %		

10. STABILITY AND REACTIVITY

- **STABILITY**
Stable
- **CONDITIONS TO AVOID**
Avoid heat, sparks and open flame.
- **INCOMPATIBILITY**
Strong oxidizers
- **HAZARDOUS DECOMPOSITION PRODUCTS**
Combustion may produce carbon monoxide, carbon dioxide and other asphyxiants.
- **HAZARDOUS POLYMERIZATION**
Will not polymerize.

11. ECOLOGICAL INFORMATION

Gasoline spills are toxic to fish and aquatic flora.

12. DISPOSAL CONSIDERATIONS

Follow federal, state and local regulations. This material is a RCRA hazardous waste. Do not flush material to drain or storm sewer. Contract to authorized disposal service.

13. TRANSPORT INFORMATION

<u>Governing Body</u>	<u>Mode</u>	<u>Proper Shipping Name</u>
DOT	Ground	Gasoline

<u>Governing Body</u>	<u>Mode</u>	<u>Hazard Class</u>	<u>UN/NA No.</u>	<u>Label</u>
DOT	Ground	3 (Flammable liquid)	1203	

14. REGULATORY INFORMATION

<u>Regulatory List</u>	<u>Component</u>	<u>CAS No.</u>
CAA - 1990 Hazardous Air Pollutants	BENZENE	71-43-2
CAA - 1990 Hazardous Air Pollutants	CUMENE	98-82-8
CAA - 1990 Hazardous Air Pollutants	ETHYL BENZENE	100-41-4
CAA - 1990 Hazardous Air Pollutants	NAPHTHALENE	91-20-3
CAA - 1990 Hazardous Air Pollutants	TOLUENE	108-88-3
CAA - 1990 Hazardous Air Pollutants	XYLENE	1330-20-7
California - Prop. 65 - Developmental Toxicity	BENZENE	71-43-2
California - Prop. 65 - Developmental Toxicity	TOLUENE	108-88-3
California - Prop. 65 - Reproductive - Male	BENZENE	71-43-2
Canada - WHMIS: Ingredient Disclosure	1,2,4-TRIMETHYLBENZENE	95-63-6
Canada - WHMIS: Ingredient Disclosure	BENZENE	71-43-2
Canada - WHMIS: Ingredient Disclosure	CUMENE	98-82-8
Canada - WHMIS: Ingredient Disclosure	CYCLOHEXANE	110-82-7
Canada - WHMIS: Ingredient Disclosure	ETHYL BENZENE	100-41-4
Canada - WHMIS: Ingredient Disclosure	LIGHT PETROLEUM DISTILLATE	8006-61-9
Canada - WHMIS: Ingredient Disclosure	N-HEXANE	110-54-3
Canada - WHMIS: Ingredient Disclosure	NAPHTHALENE	91-20-3
Canada - WHMIS: Ingredient Disclosure	TETRAETHYL LEAD	78-00-2
Canada - WHMIS: Ingredient Disclosure	TOLUENE	108-88-3
CERCLA/SARA - Haz Substances and their RQs	BENZENE	71-43-2

CERCLA/SARA - Haz Substances and their RQs	CUMENE	98-82-8
CERCLA/SARA - Haz Substances and their RQs	CYCLOHEXANE	110-82-7
CERCLA/SARA - Haz Substances and their RQs	ETHYL BENZENE	100-41-4
CERCLA/SARA - Haz Substances and their RQs	NAPHTHALENE	91-20-3
CERCLA/SARA - Haz Substances and their RQs	TETRAETHYL LEAD	78-00-2
CERCLA/SARA - Haz Substances and their RQs	TOLUENE	108-88-3
CERCLA/SARA - Haz Substances and their RQs	XYLENE	1330-20-7
CERCLA/SARA - Section 302 EHS and TPQs	TETRAETHYL LEAD	78-00-2
CERCLA/SARA - Section 313 - Emission Reporting	1,2,4-TRIMETHYLBENZENE	95-63-6
CERCLA/SARA - Section 313 - Emission Reporting	BENZENE	71-43-2
CERCLA/SARA - Section 313 - Emission Reporting	CUMENE	98-82-8
CERCLA/SARA - Section 313 - Emission Reporting	CYCLOHEXANE	110-82-7
CERCLA/SARA - Section 313 - Emission Reporting	ETHYL BENZENE	100-41-4
CERCLA/SARA - Section 313 - Emission Reporting	N-HEXANE	110-54-3
CERCLA/SARA - Section 313 - Emission Reporting	NAPHTHALENE	91-20-3
CERCLA/SARA - Section 313 - Emission Reporting	TERT-BUTYL ALCOHOL	75-65-0
CERCLA/SARA - Section 313 - Emission Reporting	TOLUENE	108-88-3
CERCLA/SARA - Section 313 - Emission Reporting	XYLENE	1330-20-7
Inventory - Canada - Domestic Substances List	1,2,4-TRIMETHYLBENZENE	95-63-6
Inventory - Canada - Domestic Substances List	BENZENE	71-43-2
Inventory - Canada - Domestic Substances List	CUMENE	98-82-8
Inventory - Canada - Domestic Substances List	CYCLOHEXANE	110-82-7
Inventory - Canada - Domestic Substances List	ETHYL BENZENE	100-41-4
Inventory - Canada - Domestic Substances List	LIGHT PETROLEUM DISTILLATE	8006-61-9
Inventory - Canada - Domestic Substances List	NAPHTHALENE	91-20-3
Inventory - Canada - Domestic Substances List	TERT-AMYL METHYL ETHER	994-05-8
Inventory - Canada - Domestic Substances List	TERT-BUTYL ALCOHOL	75-65-0
Inventory - Canada - Domestic Substances List	TETRAETHYL LEAD	78-00-2
Inventory - Canada - Domestic Substances List	TOLUENE	108-88-3
Inventory - Canada - Domestic Substances List	XYLENE	1330-20-7
Inventory - Japan - (ENCS)	1,2,4-TRIMETHYLBENZENE	95-63-6
Inventory - Japan - (ENCS)	BENZENE	71-43-2
Inventory - Japan - (ENCS)	CUMENE	98-82-8
Inventory - Japan - (ENCS)	CYCLOHEXANE	110-82-7
Inventory - Japan - (ENCS)	NAPHTHALENE	91-20-3
Inventory - Japan - (ENCS)	TERT-BUTYL ALCOHOL	75-65-0
Inventory - Japan - (ENCS)	TOLUENE	108-88-3
Inventory - Japan - (ENCS)	XYLENE	1330-20-7
Inventory - Korea - Existing and Evaluated	BENZENE	71-43-2
Inventory - Korea - Existing and Evaluated	CUMENE	98-82-8
Inventory - Korea - Existing and Evaluated	CYCLOHEXANE	110-82-7
Inventory - Korea - Existing and Evaluated	ETHYL BENZENE	100-41-4
Inventory - Korea - Existing and Evaluated	LIGHT PETROLEUM DISTILLATE	8006-61-9
Inventory - Korea - Existing and Evaluated	NAPHTHALENE	91-20-3
Inventory - Korea - Existing and Evaluated	TERT-AMYL METHYL ETHER	994-05-8
Inventory - Korea - Existing and Evaluated	TERT-BUTYL ALCOHOL	75-65-0
Inventory - Korea - Existing and Evaluated	TETRAETHYL LEAD	78-00-2
Inventory - Korea - Existing and Evaluated	TOLUENE	108-88-3
Inventory - Korea - Existing and Evaluated	XYLENE	1330-20-7
Inventory - TSCA - Sect. 8(b) Inventory	1,2,4-TRIMETHYLBENZENE	95-63-6
Inventory - TSCA - Sect. 8(b) Inventory	BENZENE	71-43-2
Inventory - TSCA - Sect. 8(b) Inventory	CUMENE	98-82-8
Inventory - TSCA - Sect. 8(b) Inventory	CYCLOHEXANE	110-82-7
Inventory - TSCA - Sect. 8(b) Inventory	ETHYL BENZENE	100-41-4
Inventory - TSCA - Sect. 8(b) Inventory	LIGHT PETROLEUM DISTILLATE	8006-61-9
Inventory - TSCA - Sect. 8(b) Inventory	NAPHTHALENE	91-20-3
Inventory - TSCA - Sect. 8(b) Inventory	TERT-AMYL METHYL	994-05-8

Inventory - TSCA - Sect. 8(b) Inventory	ETHER	
Inventory - TSCA - Sect. 8(b) Inventory	TERT-BUTYL ALCOHOL	75-65-0
Inventory - TSCA - Sect. 8(b) Inventory	TETRAETHYL LEAD	78-00-2
Inventory - TSCA - Sect. 8(b) Inventory	TOLUENE	108-88-3
NJ Department of Health RTK List	XYLENE	1330-20-7
NJ Environmental Hazardous Substances List	ETHYL BENZENE	100-41-4
NJ Environmental Hazardous Substances List	1,2,4-TRIMETHYLBENZENE	95-63-6
NJ Environmental Hazardous Substances List	BENZENE	71-43-2
NJ Environmental Hazardous Substances List	CUMENE	98-82-8
NJ Environmental Hazardous Substances List	CYCLOHEXANE	110-82-7
NJ Environmental Hazardous Substances List	ETHYL BENZENE	100-41-4
NJ Environmental Hazardous Substances List	LIGHT PETROLEUM	8006-61-9
	DISTILLATE	
NJ Environmental Hazardous Substances List	N-HEXANE	110-54-3
NJ Environmental Hazardous Substances List	NAPHTHALENE	91-20-3
NJ Environmental Hazardous Substances List	TERT-BUTYL ALCOHOL	75-65-0
NJ Environmental Hazardous Substances List	TETRAETHYL LEAD	78-00-2
NJ Environmental Hazardous Substances List	TOLUENE	108-88-3
NJ Environmental Hazardous Substances List	XYLENE	1330-20-7
NJ Special Hazardous Substances	BENZENE	71-43-2
NJ Special Hazardous Substances	CUMENE	98-82-8
NJ Special Hazardous Substances	CYCLOHEXANE	110-82-7
NJ Special Hazardous Substances	ETHYL BENZENE	100-41-4
NJ Special Hazardous Substances	N-HEXANE	110-54-3
NJ Special Hazardous Substances	TERT-BUTYL ALCOHOL	75-65-0
NJ Special Hazardous Substances	TETRAETHYL LEAD	78-00-2
NJ Special Hazardous Substances	TOLUENE	108-88-3
NJ Special Hazardous Substances	BENZENE	71-43-2
NJ Special Hazardous Substances	CUMENE	98-82-8
NJ Special Hazardous Substances	CYCLOHEXANE	110-82-7
NJ Special Hazardous Substances	ETHYL BENZENE	100-41-4
NJ Special Hazardous Substances	NAPHTHALENE	91-20-3
NJ Special Hazardous Substances	TERT-BUTYL ALCOHOL	75-65-0
NJ Special Hazardous Substances	TETRAETHYL LEAD	78-00-2
NJ Special Hazardous Substances	TOLUENE	108-88-3
NJ Special Hazardous Substances	XYLENE	1330-20-7
NJ Special Hazardous Substances	BENZENE	71-43-2
NJ Special Hazardous Substances	CUMENE	98-82-8
NJ Special Hazardous Substances	CYCLOHEXANE	110-82-7
NJ Special Hazardous Substances	ETHYL BENZENE	100-41-4
NJ Special Hazardous Substances	NAPHTHALENE	91-20-3
NJ Special Hazardous Substances	TERT-BUTYL ALCOHOL	75-65-0
NJ Special Hazardous Substances	TETRAETHYL LEAD	78-00-2
NJ Special Hazardous Substances	TOLUENE	108-88-3
NJ Special Hazardous Substances	XYLENE	1330-20-7
NJ Special Hazardous Substances	BENZENE	71-43-2
NJ Special Hazardous Substances	CUMENE	98-82-8
NJ Special Hazardous Substances	CYCLOHEXANE	110-82-7
NJ Special Hazardous Substances	N-HEXANE	110-54-3
NJ Special Hazardous Substances	TERT-AMYL METHYL	994-05-8
NJ Special Hazardous Substances	ETHER	

Title III Classifications Sections 311,312:

- Acute: **YES**
- Chronic: **YES**
- Fire: **YES**
- Reactivity: **NO**
- Sudden Release of Pressure: **NO**

15. OTHER INFORMATION

Precautionary labeling for pumps, portable containers, and drums is required. A "hazardous when empty" pictogram and D.O.T. flammable liquid label are also required for drums. Details available upon request. Because benzene is present in this product above 0.1%, the Osha Standard for benzene is applicable to work locations upstream of final discharge from terminals. Consult 29CFR1910.1028 for details. Prolonged and repeated excessive exposures to benzene can result in blood disorders ranging from anemia to leukemia. Sun recommends that exposures to benzene be kept below 1.0 ppm for 8-hours; 5.0 ppm for 15-min. Normal service station operations are below these values. For use as motor fuel only. Do not use for any other purpose. Catecholamines and similar adrenergic drugs are generally

contraindicated because of potential for increased sensitivity of the heart from hydrocarbon overexposure and subsequent ventricular fibrillation. EKG monitoring may be indicated and bronchodilators should be selected with care. Following injection, prompt debridement of the wound is necessary to minimize necrosis and tissue loss.